


Recycled Water Program

Preliminary Design Report

January 30, 2017 Workshop






- Purpose and Status
- Development and Timelines
- Production and Demand Projections
- Conveyance Systems and Use Areas
- Recommendations, Schedule and Costs
- Questions, Answers and Discussion
- Next Steps

Purpose and Status

Describe Phase 1 and Buildout of District's Recycled Water Program with respect to existing and future conditions; development projections, phasing and recycled water use areas; recommended improvements and descriptions (including costs and timeline) and implementation plan.

- Draft Report: Review and comment
- Board Approval: February or March, 2017

Proposed Developments and Timelines



D		Percent of Future Homes Occupied (%) ¹						
Development and Phase ³		2018	2020	2025	2030	2035	2040	2045
Murieta Gardens (305)	Phase 1	100						
The Retreats (88)	Phase 1	100						
Village A (167)	Buildout	<u> </u>	70	15	7	8		
Village B (167)	Buildout	<u> </u>	10	30	30	30		
Village C (130)	Buildout	L	10	40	40	10		
Village D (42)	Buildout			25	25	50		
Village E (43)	Buildout				20	80		
Village F (95)	Buildout			2	38	60		
Village G (53)	Buildout				10	90		
Village H (122)	Buildout			10	25	65		
Apartments (170)	Buildout		70	15	7	8		
Residences of Murieta Hills (198)	Buildout		100					
Lakeview (99)	Buildout	<u> </u>	100					
Riverview (140)	Buildout		100					
Industrial/Commercial/Residential (160)	Buildout		15	30	30	25		

Developments to be served recycled water

Developments not to be served recycled water

Values shown are percentages and represent the percent of total number of equivalent residential units estimated to be constructed and/or occupied by the referred date. Values shown in parentheses () represent the number of equivalent

Timeline Data Sources

- Sewer Studies & Responses (thru 2016)
 - o The Retreats
 - Retreats
 - Murieta Gardens
 - o Rancho Murieta North
- Discussions with Developer's Engineer
- Water Supply Assessment
- Title XVI Report

Proposed Developments and Use Areas

Table 1. Proposed Developments and Recycled Water Use Areas


Phase	Proposed Developments	Proposed Recycled Water Use Areas
Phase 1	Murieta Gardens	Murieta Gardens* [U, R]
	Retreats (North, West and East)	Retreats* (North, West and East) [U]
		Stonehouse Park ^b (existing) [U]
		Escuela Park ^b (existing) [U]
		Main Northgate b (existing) [U]
		District Office ^b (existing) [U]
		Commercial Loop:
Buildout	Residences of Murieta Hills	Residences of Murieta Hills* [U,R]
	Apartments	Apartments* [U]
	Industrial/Commercial/Residential	Industrial/Commercial/Residential* [U,R]
	Village A	Village A* [R]
	Village B	Village B [*] [R]
	Village C	Village C* [R]
	Village D	
	Village E	
	Village F	
	Village G	
	Village H	
	Riverview	
	Lakeview	

(R) = Future recycled water front and backyard irrigation of residential developments

⁽U) = Future recycled water irrigation of existing parks, common areas and other landscaping

Development and ADWF Projections

Figure 2



Recycled Water Production and Demand Projections

Development/Proposed Recycled Water Use Area	Description	Projected RW Demand (AFY)	Wastewater Production (AFY)		
Existing Recycled Water Use Areas					
Exising Development					
Rancho Murieta North & South Golf Courses	18-hole golf courses (~250 ac)	550	380.9		
Van Vleck Ranch	Field 1 (\sim 49ac), Field 2 (\sim 25ac), Field 3 (\sim 22 ac)	215			
Sub Total		550* / 765**	380		
Phase 1 Proposed Expanded Recycled	Water Use Areas (~2016-2020)				
Infill	0.05 MGD allocation assumed	0	56.0		
Main Northgate	Conversion to recycled water	2,8	0.0		
District Officea	Conversion to recycled water	5.4	0.0		
Retreats (North, East and West)	84 residential units	15.1	19.8		
Murieta Gardens	78 residential units, commercial equivalent to 227 residential units	30.5	71.9		
Stonehouse Park (4-acre park)	Conversion to recycled water	36.2	0.0		
Escuela Park (4-acre park)	Conversion to recycled water	12.1	0.0		
Commercial Loop (to be developed)	Potential conversion to recycled water; could be 20 to 30 AFY demand; require coordination with Owner to proceed				
	Phase 1 Sub Total	102	148		
	Sub Total	650* / 865**	530		
Phase 2 Proposed Expanded Recycled Water Use Areas (~2020-2025)					
Village A	167 residential units	56.5	39.3		
Village B	167 residential units	64.6	39.3		
Village C	130 residential units	49.6	30.6		
Village D	42 residential units	0	9.9		
Village E	43 residential units	0	10.1		
Village F	95 residential units	0	22.3		
Village G	53 residential units	0	12.5		
Village H	122 residential units	0	28.7		
Riverview	140 residential units	0	32.9		
Lakeview	99 residential units	0	21.4		
Apartments	170 residential units	23.8	23.3		
Residences of Murieta Hills	198 residential units	73.8	46.6		
Industrial/Commercial/Residential	160 equivalent residential units	50.9	37.6		
Van Vleck Ranch	Sprayfield 4	410			
	Phase 2 Sub Total	320* / 730**	355		

Current Capacity: 3,265 ERUs

Existing 2,604 ERUs

Development (Sewer Studies)

Murieta Gardens

Residential 78 ERUs

Commercial 227 ERUs

Retreats 84 ERUs

Subtotal 389 ERUs

Remaining 272 ERUs

Infill (PDR assumption) 238 ERUs


(0.05 MGD)

^{**} Beneficial reuse plus Van Vleck sprayfield disposal demands


Production and Demand Projections

Sources of Data:

- Sewer Studies & Responses (thru 2016)
 - o The Retreats
 - o Retreats
 - o Murieta Gardens
 - o Rancho Murieta North
- Discussions with Developer's Engineer
- Title XVI Report







Existing Recycled Water Conveyance Systems and Use Areas




Table 6. Recycled Water Conveyance System Roles and Responsibilities

System and Facility	Ownership and O&M Costs		
	District	RMPI ^b	RMCC
Equalization Basin	X		
South	h Golf Course		
Equalization Basin - Lakes 16 & 17 Pipeline	С		с
Lake 16 & 17 - Lake 10 & 11 Pipeline		D	d
North	h Golf Course		
Recycled Water Pump Station	С		С
North Golf Course Force Main to Yellow	С	С	
Bridge Pipeline			
North Golf Course Force Main from Yellow		E	е
Bridge to Bass Lake Pipeline			

Adapted from Agreement for Availability and Use of Reclaimed Water (May 17, 1988) and the Amendment to Agreement for Availability and Use of Reclaimed Water (May 4, 1994)

Condition Assessment: High Risk

Other Concerns:

Location or condition unknown, potential change in ownership

Impacts rehabilitation strategy for existing 12-inch sewer force main

^b Rancho Murieta Properties, Inc. (RMPI) was the original owner, current owner is Rancho North Properties, LLC .


RMCSD to own, operate and maintain; operation and maintenance costs to be split 50/50 between RMCSD and RMCC.

 $^{^{}m d}$ RMPI to own, RMCC to operate and maintain; operation and maintenance costs to be split 50/50 between RMPI and RMCC.

e RMPI to own, RMCC to operate and maintain.

Hydraulic Modeling (Buildout Only)


Condition Assessment; Not PDR



Impacts both condition assessment & PDR

Next Steps (Separate from PDR): Expand model capabilities, optimize system, surge & detail design

Recycled Water Conveyance Future



Use of System (limitations)

- Separate timeframes for golf course supply and U& R irrigation
- Dictates max operating pressures & flow
- Requires additional supplies (storage tanks) and controls
- Unknown condition, location & potential change in ownership

Next Step: Phase 2 condition assessment

Recommended Improvements – Phase 1

Table 10. Recommended Phase 1 Recycled Water Improvements Features and Components


	ocess / Element	Criteria / Feature		
	Recycled Water SCADA Control System	,		
	Number of SCADA Terminals	1		
	Location	WWRP		
	Туре			
	Lookout Hill	Programmable Logic Controller (PLC)		
	Control Valves	Remote Terminal Units		
	Communication	Radio*		
	Control	Pressure		
2.	Equalization Basin Potable Water Air Gap Conn	ection		
	Flow Rate (maximum)	900 gpm		
	Diameter	8-inch		
	Material	Ductile Iron		
	Air Gap (90° Bend)	16 inches per RW-17		
3.	Rehabilitate Existing Recycled Water Pumping			
	Pump Type	Vertical Turbine		
	Number of Pumps	Two (2) duty; one (1) stand by		
	Total Dynamic Head	325 feet		
	Pump Flow	1,500 gpm		
	Motor Horsepower	200 HP		
	Backup Power	200 KW Standby Diesel Generator		
	Control Method	Pressure		
4.	District Headquarters Conversion - Recycled W	ater Irrigation System Connection		
	Site Supervisor	District (Paul Siebensohn)		
	Type of Landscape	Grass in front yard and medians		
	Type of Irrigation	Spray and drip		
	Area (approximate)	168 acres		
	Water Demand (estimated)	5.4 AFY		
	Pipe Diameter	4-inch		
	Pipe Material	PVC		
5.	Northwest Recycled Water Transmission Main			
	Pipeline Length (total)	11,600 lineal feet, total		
	Highway 16 Undercrossing	1,000 lineal feet (approximately)		
	Legacy Lane to Lookout Hill Tank	2,800 lineal feet (approximately)		
	Lookout Hill Tank to 12-inch Force Main	2,400 lineal feet (approximately)		
	12-inch Force Main along Stonehouse Road to	5,400 lineal feet (approximately)		
	Stonehouse and Escuela Parks			
	Replace	1,200 lineal feet of 12-inch		
	CIPP Rehabilitation	2,400 lineal feet of 12-inch		
	Diameter	12 inch		

Process / Element	Criteria / Feature
Buried Pipeline Materials	PVC or HDPE pipe
Above Grade Pipeline Materials	Steel or Ductile Iron pipe
Pipeline Labeling	"Recycled Water, Do Not Drink"
Pipe Color or Wrapping	Purple or wrapped with purple tape
Air and Blowoff Valves	District Standards
Others	See District Standards
6. Lookout Hill Booster Pumping Station	
Pump Type	Vertical Turbine
Number of Pumps	One (1) duty; one (1) stand by
Total Dynamic Head	150 feet TDH
Pump Flow	1,000 gpm (maximum)
Motor Horsepower	50 HP
Pump Housing	Not required
Backup Power	50 KW Standby Diesel Generator
Control Method	Pressure
7. Escuela Park Conversion - Recycled W	ater Irrigation System Connection
Site Supervisor	Rancho Murieta Association (RMA) (TBD)
Type of Landscape	Plantings and flowers now
Type of Irrigation	Spray and drip
Area (approximate)	4 acres
Water Demand (estimated)	12.1 AFY
Pipe Diameter	4-inch
Pipe Material	PVC
B. Stonehouse Park Conversion - Recycle	ed Water Irrigation System Connection
Site Supervisor	RMA (TBD)
Type of Landscape	Grass primarily (fields)
Type of Irrigation	Spray and drip
Area (approximate)	4 acres
Water Demand (estimated)	36.2 AFY
Pipe Diameter	4-inch
Pipe Material	PVC
9. Lookout Hill Recycled Water Storage T	ank
Number of Tanks	1
Diameter	40
Height (maximum at sidewall)	26
Volume (nominal)	200,000 gallons
Materials of Constructed	Bolted Steel
10. North Maingate Conversion - Recycle	
Site Supervisor	RMA (TBD)
Type of Landscape	Grass, flower beds, plantings
Type of Irrigation	Spray and drip
Area (approximate)	121 acres
Water Demand (estimated)	2.8 AFY
Pipe Diameter	4-inch
Pipe Material	PVC

Recommended Improvements - Phase 1



Figure 12. Proposed Phase 1 WWRP Improvements



Conversions from Potable to Recycled Water

Figure 14



Proposed District Headquarters Conversion






Recommended Improvements – Buildout

Process / Element	rovements Features and Components Criteria / Feature	
A. Disinfection Facilities Upgrade	<u>'</u>	
Existing Contact Basin Modal Contact Time	27 minutes at 3.0 MGD1	
Required Modal Contact Time	90 minutes (minimum)	
Additional Modal Contact Time Required	63 minute (minimum)	
New Contact Basin Efficiency	90%	
(Assumed Baffling Factor)	5070	
Required Contact Basin Volume	145,835 gal, minimum; 146,610 gal actu	
Length to Width to Depth Ratios	Target 40:1:1.5; Actual 40:1:1.4	
Length (without walls)	280 ft total (3 passes, each at 93.33 ft long	
Width (without walls)	21 ft total (3 passes, each at 7 ft wide)	
Depth (without walls)	10 ft	
B. North Golf Course Conveyance System Rehabilita		
WWRP to Bass Lake	11,200 lineal feet (12- and 8-inch)	
Replacement	4.300 lineal feet (12- and 6-men)	
CIPP Rehabilitation	3.800 lineal feet, 8-inch	
Replacement	1,900, 8-inch	
	1,900, 8-IIICII	
C. Bass Lake Recycled Water Storage Tank Number of Tanks	1	
Diameter	70	
Height (maximum at sidewall)	22	
Volume (nominal)	500,000 gallons	
Materials of Constructed	Bolted Steel	
D. Bass Lake Booster Pumping Station	I	
Pump Type	Vertical Turbine	
Number of Pumps	One (1) duty; one (1) stand by	
Total Dynamic Head	120 feet	
Pump Flow	1,200 gpm	
Motor Horsepower	50 HP	
Pump Housing	Not required	
Backup Power	50 KW Standby Diesel Generator	
Control Method	Pressure	
E. Seasonal Storage Reservoir		
Existing Storage Capacity	728.2 AF	
Required Storage Capacity (Buildout)	765 AF	
Incremental Capacity Upgrade	40 AF	
F. Van Vleck Sprayfield No. 4		
Extension of Recycled Water Transmission Main	1,000 lineal feet of 12-inch Certa-Loc™	
Sprayfield 4 Transmission Main	5,000 lineal feet of 8-inch Certa-Loc™	
Sprayfield 4 Transmission Main	5,000 lineal feet of 6-inch Certa-Loc™	
Sprayfield 4 Transmission & Distribution Mains	16,250 lineal feet of 4-inch Certa-Loc™	
Irrigation System	55 K-line Strings	
Depth of Cover	None, all located aboveground	
G. Dissolved Air Flotation Feed Pump Improvemen		
Replacement of 3rd Feed Pump	\$100,000 Allocation	
See Figure 1-3 of WWRP Modified Chlorine Contact Disinfection Sy.		

Proposed Implementation Schedule



Recommended Next Steps:

- Review and comment
- Adopt PDR
- Initiate Phase 2 condition assessment
- Initiate environmental review and detailed design
- Continued development submittal reviews (sewer studies & irrigation plans)

Estimated of Probable Construction Costs

Table 15. Recommended Recycled Water Improvements and Estimated Costs

Phase 1 Recycled Water SCADA Contro Equalization Basin Potable Wa Recycled Water Pumping Station District Headquarters Convers Northwest Recycled Water Tra Lookout Hill Booster Pumping Escuela Park Conversion Stonehouse Park Conversion Lookout Hill Recycled Water State Recycled Water State Lookout Hill Recycled Water S	ter Air Gap on ion nsmission Main Station	250,000 76,000 1,045,000 20,000 1,441,000 612,000 16,000 36,000		
2 Equalization Basin Potable Wa 3 Recycled Water Pumping Station 4 District Headquarters Convers 5 Northwest Recycled Water Tra 6 Lookout Hill Booster Pumping 7 Escuela Park Conversion 8 Stonehouse Park Conversion	ter Air Gap on ion nsmission Main Station	76,000 1,045,000 20,000 1,441,000 612,000 16,000 36,000		
3 Recycled Water Pumping Station 4 District Headquarters Convers 5 Northwest Recycled Water Tra 6 Lookout Hill Booster Pumping 7 Escuela Park Conversion 8 Stonehouse Park Conversion	on ion nsmission Main Station	1,045,000 20,000 1,441,000 612,000 16,000 36,000		
4 District Headquarters Convers 5 Northwest Recycled Water Tra 6 Lookout Hill Booster Pumping 7 Escuela Park Conversion 8 Stonehouse Park Conversion	ion nsmission Main Station	20,000 1,441,000 612,000 16,000 36,000		
5 Northwest Recycled Water Tra 6 Lookout Hill Booster Pumping 7 Escuela Park Conversion 8 Stonehouse Park Conversion	nsmission Main Station	1,441,000 612,000 16,000 36,000		
6 Lookout Hill Booster Pumping 7 Escuela Park Conversion 8 Stonehouse Park Conversion	Station	612,000 16,000 36,000		
7 Escuela Park Conversion 8 Stonehouse Park Conversion		16,000 36,000		
8 Stonehouse Park Conversion	torage Tank	36,000		
	torage Tank	_		
9 Lookout Hill Recycled Water St	torage Tank	7 . 7		
		545,000		
10 Main NorthgateConversion		18,000		
11 Commercial Loop Conversion		TBD		
Phase 1 Subtotal (E	stimated Construction Cost)	4,060,000		
12 Soft Costs - 32.5% (Admin., Re	g., Eng., Construct Man.)	1,319,500		
	Phase 1 Total (Project Cost)	5,380,000b		
Buildout Recycled Water Improvements				
13 SCADA Upgrades		82,000		
14 Disinfection Facilities Upgrade		665,000		
15 North Golf Course Conveyance	System	1,620,000		
16 Bass Lake Tank		1,216,000		
17 Bass Lake Booster Pumping St.	ation	625,000		
18 Seasonal Storage Reservoir Ex	pansion	839,000		
19 Van Vleck Sprayfield 4		890,000		
20 DAF Pumping Replacement		100,000		
Buildout Subtotal (E	stimated Construction Cost)	6,030,000c		
21 Soft Costs - 32.5% (Admin., Re	g., Eng., Construct Man.)	1,960,000		
I	Buildout Total (Project Cost)	7,990,000		
Phase 1 and Buildout Recycled Water Improvements				
Grand Total (Phase 1 and Build		13,400,000d		
Estimated Number of New Equ	ivalent Residential Units	2,213		
Estimated Cost per Connection	(\$/ERU)	\$6,055		

Estimated Cost per Connection (\$/ERU)	\$6,055
* Estimated costs based upon Engineering News Record (ENR) 20 City Average Co	nstruction Cost Index (CCI) at 10,385
(1	

b Compared to \$10,014,000 (\$9,100,000 adjusted for inflation) as described previously in the District's Title XVI Recycled Water Feasibility Study

Phase 1 (\$M): Construction: Project:	4.06 5.38
Buildout (\$M) Construction: Project:	6.03 7.99
Total Combined (\$M):	13.40
Future ERUs:	2,213

Compared to \$15,055,000 as described previously in the District's Title XVI Recycled Water Feasibility Study

⁴ Compared to \$25,070,000 as described previously in the District's Title XVI Recycled Water Feasibility Study

Recommended Next Steps

Obtain Board feedback and adoption (February / March, 2017)

Input regarding the following next:

- Phase 2 condition assessment
- Hydraulic modeling
- Environmental review and detailed design timeline









- OE3 7.8 ac along Cantova Way
- 1 ac Plaza Shopping Center
- 26 AFY demand in 2013

Recommended Next Step: Discuss with Owner, obtain and review as-builts; field verify. Assess cost effectiveness

Proposed System Controls & Time of Use





Sewer Studies

~ Preliminary Sewer Study for Rancho Murieta North ~

PRELIMINARY SEWER STUDY FOR RANCHO MURIETA NORTH

Ranch Murieta- County of Sacramento, California

March 31, 2016



Brandon Morland BAKER-WILLIAMS ENGINEERING GROUP 6020 Rutland Drive, Suite #19 Carmichael, California 95608 PH: 916-331-4336

Baker-Williams Engineering Group



SEWER STUDY

FOR

MURIETA GARDENS I & II

IN

Rancho Murieta County of Sacramento, California

May 15, 2016

SEWER STUDY

FOR

The Retreats North & East

IN

Rancho Murieta County of Sacramento, California

May 6, 2016

Prepared by

Brandon Morland
BAKER-WILLIAMS ENGINEERING GROUP
6020 Rutland Drive, Suite #19
Carmichael, California 95609
PH: 916-331-4336
Fax: 916-331-4430



SEWER STUDY

FOR

THE RETREATS WEST

II

Rancho Murieta County of Sacramento, California

May 3, 2016

Prepared by:

Brandon Morland
BAKER-WILLIAMS ENGINEERING GROUP
6020 Rutland Drive, Suite #19
Carmichael, California 95608
PH: 916-331-4438
Fax: 916-331-4430

